



PRODUCT DATA SHEET

Monarflex Extreme T Plus

High Strength Scaffold Sheeting

High strength reinforced low density polyethylene.

- Patented eyelet design
- Unique high performance Anchor & Strap fixing system
- Suitable for screen printing
- Available in flame retardant version

TECHNICAL DETAILS	
Material	High strength reinforced Low Density Polyethylene (LDPE) with plastomer & UV stabilizer
Roll Size / Weight	2m x 45m (24kg) +/-5%
Colour	Clear with white eyelets
Grid	8mm x 8mm PET MUJ 1670 dtex
Thickness	0.2mm
Weight per m ²	256g/m ²
Tensile Strength	900N/50mm +/-60N / 50mm
Eyelet Pullout	970N
Eyelets per Roll	270
Light Transmission	>80%
Conforms to	BS 7955, BS 8093 CP for use of scaffold sheets
Application	External use

Icopal Ltd

Barton Dock Road

Stretford

Manchester M32 0YL

Tel: 0161 865 4444

Fax: 0161 865 8433

--	--	--	--

PRODUCT DATA SHEET

Monarflex Extreme T Plus

High Strength Scaffold Sheeting

Please NOTE: This information is given in good faith being based on the latest knowledge known to Anderson Monarflex Ltd. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

The above figures are subject to a tolerance of +/- 5%.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.

Icopal Ltd

Barton Dock Road
Stretford
Manchester M32 0YL
Tel: 0161 865 4444
Fax: 0161 865 8433