



PRODUCT DATA SHEET

Monarflex Scaffband Flamesafe

Scaffold Sheeting

Economy sheeting recommended for use in low rise, shorter term projects that are not exposed to high wind risk.

- Choice of high performance Flexities or Euroties fixing systems
- Lightweight for easy handling on site and suitable for DigiWrap printing

TECHNICAL DETAILS	
Material	Reinforced Low Density Polyethylene (LDPE) with flame retardant formulation and UV stabilization
Roll Size / Weight	2m x 45m (17kg) +/-5% 3m x 45m (25kg) +/-5%
Colour	White with 3x70mm white HDPE FR tapes (5 on 3 metre)
Grid	9mmx12mm polyester grid, yarns 2200/1670 dtex
Thickness	0.12mm +/-5%
Weight per m2	180g/m2 +/-5% 3m 185g/m2 +/-5%
Light Transmission	>50%
Tensile strength	690N / 50mm +/-30N/50mm
Eyelet Pullout	>700N
Eyelets / Bands	At 100mm centres on three reinforced bands of 7cm positioned horizontally along the width of the sheet. 5 bands on 3 metre
Flame Retardant	According to EN 13501-1 Class B Conforms to LPS 1215 BS 476:Part 12 Ignition Sources C & G
Conforms to	BS 7955,BS 8093 CP for use of scaffold sheets
Use	External only

Icopal Ltd

Barton Dock Road

Stretford

Manchester M32 0YL

Tel: 0161 865 4444

Fax: 0161 865 8433

www.icopal.co.uk

--	--	--	--	--

PRODUCT DATA SHEET

Monarflex Scaffband Flamesafe

Scaffold Sheeting

Please NOTE: This information is given in good faith being based on the latest knowledge known to Anderson Monarflex Ltd. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

The above figures are subject to a tolerance of +/- 5%.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.

Icopal Ltd

Barton Dock Road

Stretford

Manchester M32 0YL

Tel: 0161 865 4444

Fax: 0161 865 8433

www.icopal.co.uk